

Fire detection and evacuation solutions that save lives.

XP95 Intrinsically Safe Addressable Manual Call Point

- ✓ IP67 Rated.
- ✓ 'Plug and Play' terminal connections for fast wiring.
- ✓ Continuity Link for wiring testing before commissioning.
- ✓ Reports an alarm in under 0.2 seconds.
- ✓ Resettable element.
- ✓ Anti tamper facility.
- ✓ Universal key for test and maintenance access.

Product Overview

The XP95 Intrinsically Safe (I.S.) Addressable Manual Call Point (MCP) has been designed to operate on a loop of intelligent addressable fire detection devices and when activated interrupts the polling cycle for a very fast response.

Designed specifically for use in atmospheres in which explosive mixtures are or may be present, or in areas where certain design considerations must be observed.

The address of MCP is set at the commissioning stage by means of a seven-segment DIL switch located inside the device. The device has an easily resettable element rather than a break glass and also features a unique 'Plug and Play' installation concept designed specifically to reduce installation time.

A single bi-coloured alarm LED is provided on the XP95 I.S. Addressable MCP. This LED is controlled independently of the device, by the main fire control panel. The LED is illuminated red when the MCP has been activated. Once activated, the MCP can be reset by inserting the test key into the bottom of the device.

The XP95 I.S. Addressable MCP complies with the requirements of the ATEX Directive, IECEx and the Constructive Products Directive.

To provide additional protection against accidental operation, a transparent hinged cover is available which can be fitted to the XP95 I.S. Addressable MCP.



XP95 Intrinsically Safe Addressable Manual Call Point

Specifications

Supply Voltage	14 - 22 V DC
Quiescent Current	300
Alarm Current	2mA (Alarm LED On)
Dimensions (inc. Back Box)	H 93 x W 97.5 x D 71 mm
Material	High Impact ABS
Operating Temperature	-20°C to +60°C (T4) -20°C to +40°C (T5)
Humidity	0 - 95% Non-Condensing
IP Rating	IP67
Weight	240 grams
Approvals	EN 54-11
Certification	ATEX EEx ia IIc T5, IECEx

Item Numbers

Australia

201-0107	XP95 I.S. Manual Call Point Standard Red No Flap
213-0064	Transparent Hinged Cover

International

55200-940APO	XP95 I.S. Manual Call Point Standard Red No Flap
26729-152	Transparent Hinged Cover