

## Vantage Combi – Sounder Beacon

### Features

- Selectable Signals to AS1670.4 and NZS4512
- High Brightness LED Strobe
- Selectable Output Levels
- High Output Level – up to 100dB
- Low Current Consumption
- 2 or 3 Wire Configuration
- Automatic Two Stage Signal Facility
- Excellent Lateral Sound Dispersion
- Built-in Synchronisation
- Quick-Fit Surface Mounted
- Deep Base Option
- Locking Mechanism

### Description

The Vantage Combi is a combined low profile electronic reflex horn sounder incorporating a high output LED cluster strobe light array. The Vantage Combi has been designed for general purpose, fire and security applications and incorporates both AS1670.4 and NZS4512 compliant signals.

The Vantage Combi can be configured for two or three wire operation. In two wire mode, an option for automatic 60 second alert to evacuate two stage switching is provided. In three wire mode, the fire panel controls the alert and evacuate tones.

Available in Red or White fire retardant ABS plastic, the Vantage Combi offers a quick fit bayonet mounting arrangement for faster installation and a locking system to secure the product in place. A shallow base incorporating cable entry points to the rear is supplied as standard for indoor use. An optional deep base is available which provides conduit entry access and weatherproof IP rating.

Integral switches enable the installer to select from a number of standard features which include the facility to select from three volume settings. This allows individual sounders to be retro-converted to high output devices where additional sound output is required.

Multiple Vantage Combi's may be connected together on the same sounder circuit with synchronisation maintained through use of on-board timing circuit and negates the need for a third 'timing control' wire.



Vantage Combi Sounder Beacon

### Item Numbers

Item No	Description
205-0066	Vantage Combi Red with Shallow Base
205-0067	Vantage Combi White with Shallow Base
205-0064	Deep Base only Red
205-0065	Deep Base only White

### Specifications

Operating Voltage	18 - 35V DC		
Current at 27VDC	Low	Med	High
	11mA	19mA	48mA
Output Level dB at 1M	78dB	92dB	100dB
Signal Only Output			
Australia	AS1670.4		
New Zealand	NZS4512		
Operating Temp.	-20°C +70°C		
Humidity	0 to 95% Non-condensing		
Dimensions			
with Shallow Base	94mm Dia x 90mm		
with Deep Base	94mm Dia x 107mm		
IP rating			
with Shallow Base	IP43 (indoor use)		
with Deep Base	IP65 (weatherproof)		
Weight			
with Shallow Base	223g		
with Deep Base	253g		