

Fire detection and evacuation solutions that save lives.



Features

- Certified to AS 7240-5, 7, 11, 25 and NZS 4512:2010
- Analogue Addressable System Expansion
- Wireless
- Eliminates Cabling Difficulties.
- Minimises Disruptions.
- Enables Rapid Retrofit.
- Preserves Aesthetics.

Fire detection and evacuation solutions that save lives.




Xpander is a system in which individual detectors, call points, interfaces and alarm devices communicate with the analogue addressable loop by radio signals.

A loop-powered Xpander interface controls up to 31 Xpander wireless devices. Each Xpander device is assigned a loop address with the exception of the combined devices, which occupy 2 addresses (31 combined devices use 62 addresses on the control panel). Each address is recognised by the control panel in the same way as other addressable devices connected

directly to the detection loop wiring.

Multiple Xpander interfaces can be installed on each site.

Xpander can be incorporated into fire detection systems in stately homes and architecturally sensitive buildings where the use of fire cables is either impractical or undesirable.

All of the products within the Xpander range are approved to AS 7240-25 and NZS 4512 which is the industry standard for radio equipment used in fire safety areas.

- Easy to install
- Compatible with LoopSense & FireFinder Plus
- XPERT card addressing
- Self-monitoring
- Proven technology
- 915MHz radio channels
- Up to 31 devices per interface
- Up to 5 interfaces per loop



Xpander Optical Smoke Detector & Mounting Base
4106-5303



Xpander Heat Detector & Mounting Base
4106-5301 (A1R)
4106-5302 (CS)



Xpander Multisensor Smoke Detector & Mounting Base
4106-5304



Xpander Combined Sounder & Detector
4111-1303 (Optical)
4111-1301 (A1R)
4111-1302 (CS)
4111-1304 (Multi)



Xpander Combined Sounder Visual Indicator & Detector Red Visual Indicator
4111-1401 (A1R)
4111-1402 (CS)
4111-1403 (Optical)
4111-1404 (Multi)



Xpander Combined Sounder Visual Indicator & Detector Clear Visual Indicator
4111-1501 (A1R)
4111-1502 (CS)
4111-1503 (Optical)
4111-1504 (Multi)



Xpander Manual Call Point
4105-5001



Xpander Sounder with Mounting Base
4107-8301 (Red)
4107-8302 (White)



Xpander Sounder Visual Indicator with Mounting Base
4107-8303 (Red)
4107-8304 (Clear/White Base)
4107-8305 (Amber/White Base)

Components

- 4106-5201**
A1R Heat Detector
- 4106-5202**
CS Heat Detector
- 4106-5203**
Optical Detector
- 4106-5204**
Multisensor Detector
- 4106-5100**
Detector Base
- 4111-1100**
Sounder Detector Base
- 4111-1101**
Sounder Beacon Detector Base
- 4107-8101**
Sounder Base Red
- 4107-8201**
Sounder Red
- 4107-8203**
Sounder Beacon Red



Xpander Diversity Interface
4110-2001



Xpander Hub & Cluster
4110-2004 (Radio Hub)
4110-2005 (Comms Cluster)



Xpander Diversity Survey Kit
4112-1001



Xpander Input/Output Unit
4110-2002 (Single)
4110-2003 (Dual)