

Fire detection and evacuation solutions that save lives.

XP95 Intelligent Triple IR3 Flame Detector

Features

- Detects through films of oil, dust, water and ice
- Responds to flickering flames, including those invisible to the naked eye
- False alarms due to lighting or flickering sunlight are minimised
- Compatible with Discovery and XP95 protocols
- Loop-powered
- 90° field of view
- Up to 40m coverage
- IP65 rated

Description

The XP95 Intelligent Triple IR3 Flame Detector is designed to protect areas where open flaming fires may be expected. The IR3 is sensitive to low frequency, flickering infra-red radiation emitted by flames during combustion. Since it responds to flickering radiation the IR3 Flame Detector can operate even if the lens is contaminated by a layer of oil, dust, water vapour or ice.

The Intelligent Triple IR3 Flame Detector is set to respond to low frequency radiation at 1 to 15Hz (1to 2.7µm) in order to detect all flickering flames, including those invisible to the naked eye, e.g. those emitted by hydrogen fires.

The XP95 Intelligent Triple IR3 Flame Detector has three IR sensors that respond to different IR wavelengths in order to discriminate between flames and spurious sources of radiation. False alarms due to such factors as flickering sunlight are avoided by a combination of filters and signal processing techniques.

The flame detector is loop powered and needs no external supply. The flame detector should be positioned at the perimeter of the room, pointing directly at the area of the anticipated flame or at the centre of the area to be protected. If the flame detector cannot see the whole of the area to be protected, one or more additional detectors may be required.

Flame detectors are used when detection is required to be unaffected by convection currents, draughts or wind.

Applications

- Agriculture – grain and malt processing
- Aircraft Hangars
- Automotive industry – spray booths, parts manufacture
- Chipboard and MDF manufacture
- Metal fabrication and Power Plants



Intelligent IR3 Flame Detector

Item Numbers

Australia

201-0188 XP95 Triple IR3 Flame Detector

201-0189 Flame Detector Bracket

201-0190 S/Steel Weather Shield

International

55000-020APO XP95 Triple IR3 Flame Detector

29600-203 Flame Detector Bracket

29600-206 S/Steel Weather Shield

Specifications

Supply Voltage	17-28V DC
Quiescent Current	2.2mA
Alarm Current	4.2mA
Dimensions inc base	142 x 108 x 82mm
Cable Gland Entries	2 x 20mm
Operating Range	0.1m ² n-heptane at 25m 0.2m ² n-heptane at 35m 0.4m ² n-heptane at 45m
Operating Temperature	-10°C to +55°C
Relative Humidity	0 – 95% non-condensing
IP Rating	IP65
Weight	2kg
Approval	EN54-10