

CSIRO Verification Services Clayton, Victoria, Australia +61 13 0036 3400 https://activfire.csiro.au

Certificate of Conformity

 Certificate num.
 Registration date
 Version
 Valid until

 afp - 3691
 30-Aug-2022
 Number 1 ssue date 30-Aug-2022
 30-Apr-2024

Product designation

Ampac, Models 4210-0058 / 4210-0059, zone input device

(Refer to the Schedule/enclosures for further specified details)

Agent/distributor

Ampac Pty Limited

7 Ledgar Road, BALCATTA, WA, AUSTRALIA, 6021

Registrant

Ampac Pty Limited

7 Ledgar Road, BALCATTA, WA, AUSTRALIA, 6021

Producer

Ampac Pty Limited

7 Ledgar Road, BALCATTA, WA, AUSTRALIA, 6021

Conformance criteria and evaluation

The Ampac, Models 4210-0058 / 4210-0059, zone input device has been evaluated and verified as conforming with the relevant requirements of the following criteria.

- 1. Australian Standard AS ISO 7240.17:2021, 'Fire detection and fire alarm systems Part 17: Transmission path isolators'.
- Australian Standard AS ISO 7240.18:2018, 'Fire detection and alarm systems Part 18: Input/output devices'.

Limitations/conditions of conformance

Limitations/conditions of conformance, where identified on this certificate, are derived from qualifications from evaluation(s) for conformity and/or other related technical documentation. All details with respect to design, assembly and installation instructions and restrictions should be checked against the producer's current technical manual/data sheets and the requirements of the Authority having Jurisdiction.

This certification is issued within the scope of CSIRO Verification Services – Rules governing ActivFire Scheme and is valid only for the product(s) as submitted for evaluation and verification of conformity, subject to the following conditions.

- Reference to details, limitations and requirements, where documented as a schedule/enclosure with this certificate.
- The Registrant is responsible for their attestation of conformity and ensuring that on-going production complies with the conformance criteria defined in this certificate.
- This certificate will not be valid if any changes or modifications are made to the product which have not been notified and validated by CSIRO Verification Services.
- This certificate is subject to periodical re-validation upon verification that all requirements, as determined by the conformity assessment body, continue to be satisfactorily met by the Registrant.
- This certificate may only be reproduced in its published form, without modification and inclusive of all schedules/enclosures.
- Any changes, errors or omissions, must be submitted in writing and if necessary or requested, substantiated with relevant evidence.
- Any representations, such as advertising or other marketing related activities or articles shall reflect the correct contents of this certificate and conform with all relevant trade practices .and consumer protection legislation and regulations.
- Any terms or conditions of use as applicable to content and documentation as published or accessed through web sites administered by the CSIRO Verification Services.

Issued by

David Whittaker

Executive Officer - ActivFire Scheme





Schedule to

Certificate of Conformity

Certificate num.	Registration date	V	ersion	Valid until	
afp - 3691	30-Aug-2022	Number 1	Issue date 30-Aug-2022	30-Apr-2024	Page 2 of 3

Producer's description

The Ampac, Models 4210-0058 / 4210-0059, zone input device is designed to allow up to 40 conventional detectors to be interfaced to the Ampac range of Apollo analogue addressable control panels.

The programmable End of Line (EOL) feature, incorporating Alarm Verification Facility (AVF), provides options for $3K3\Omega$ or $6K2\Omega$ resistor values. To facilitate support for detector head removal, a 10uF capacitor can also be selected for use with the appropriate diode bases on the conventional detection circuit.

The Ampac, Models 4210-0058 / 4210-0059, zone input device is loop powered and incorporates bi-directional isolation circuitry to provide protection against detection loop short circuits. On board LED status indication is provided for service and commissioning purposes.

Technical specification

The following details are a representative extract of the technical specification for the Ampac, Models 4210-0058 / 4210-0059, zone input device and may be subject to change. Complete and current details should be determined from the designated producer's technical manual/data sheets.

Schedule of variant designations

The following is a schedule of validated variant designations of the certified/listed equipment.

Variant		
Туре	Ident	Description
Item No	4210-0058	DIN mount, loop powered, zone input device with bi-directional short circuit isolation
(Model) 4210-00		Surface mount, loop powered, zone input device with bi-directional short circuit isolation

Schedule of properties/characteristics

The following schedule is an extract of physical and operational properties/characteristics of the certified/listed equipment.

Item No.	4210-0058	4210-0059	
Mount, enclosure	DIN	Surface, enclosed	
Operating voltage	17 to 28 Vdc (nominal voltage 27 Vdc)		
	3K3 EOL: 7.5 mA		
Quiescent current	6K2 EOL: 5 mA		
	1uF EOL: 2 mA		
Alarm condition current	23 mA		
Operating Temperature	-20°C to 70°C		
Humidity	0 to 95% RH (non-condensing or icing)		
Dimensions 150 mm H x 110 mm W x 25 r		150 mm H x 200 mm W x 52 mm D	
Material	Grey ABS		
IP rating	- IP44		

Schedule of transmission path isolator characteristics

The following is schedule of transmission path isolator characteristics of the certified/listed equipment.

Parameter	Description	Value
V_{max}	Maximum line voltage	28 Vdc
V_{min}	Minimum line voltage	17 Vdc
V _{SO max}	Maximum voltage device isolates	16 Vdc
$V_{SO\;min}$	Minimum voltage device isolates	12 Vdc
V _{SC max}	Maximum voltage device reconnects	17 Vdc
V _{SC min}	Minimum voltage device reconnects	12 Vdc
I _{C max}	Maximum rated current	1 A
I _{S max}	Maximum rated switch current	3.3 A
I _{L max}	Maximum leakage current (test pulse)	60 mA
Z _{C max}	Maximum series impedance switch closed	100 mΩ

Schedule to Certificate of Conformity

Certificate num. Registration date Version Valid until

afp - 3691 30-Aug-2022 1 30-Aug-2022 30-Apr-2024

Page 3 of 3

Supplementary information

Schedule of relevant articles

The following schedule is an extract of articles significant and/or related as evidence of conformity.

Reference			Date issued	
Туре	Ident.	Title / description	(or date validated)	Source
Report	XF3359/R2	Evaluation for Conformity of the AMPAC 4210-005x series input output and zone interfaces to the requirements of AS ISO 7240.18:2018 and AS ISO 7240.17:2021	25-Aug-2022	CSIRO Fire Systems Laboratory, AU.
Document	PDS4210-0058-2 DRAFT	AMPAC Advanced Warning Systems Ampac Zone Input Output Device	7-Apr-2022	
	MAN3053-1	AMPAC Advanced Warning Systems Zone Input Device – Installation Guide Item Number – 4210-0058 & 4210-0059	17-Sep-2013	Ampac Pty Limited, AU
	MAN3052-1	AMPAC Advanced Warning Systems Input Output Device Range – Installation Guide Item Numbers – 4210-0050 to 4210-0057	17-Sep-2013	