

Fire detection and evacuation solutions that save lives.

Manual Call Point – ACP-02

Features

- Key re-settable
- No frangible glass to replace after operation
- Quick reset without disassembly
- Foolproof testing by actual operation
- Double action operation
- Compact design
- Wire protected connectors
- High reliability toggle switch operation
- Standard conduit size cable entry
- Simple highly visible operating instructions
- Cost effective installation and maintenance

Description

The AMPAC ACP-02 double action re-settable Manual Call Point (MCP) eliminates the possibility of accidental operation.

The first action of pushing the front transparent cover will cause it to drop down to allow access to a toggle switch. The second action is that of operating the toggle switch to initiate an alarm at the associated Fire Alarm Control Panel

The AMPAC ACP-02 Manual Call Point is manufactured from high impact, UV stabilised heat resistant ABS and is available in four (4) models:

- Conventional red surface mounted
- Conventional red flush mounted
- Addressable red surface mounted
- Addressable red flush mounted

The flush mounted versions require an optional standard wall box.

Application

- Points of egress
- Nursing Homes
- Child care centres
- General office areas



ACP-02 Manual Call Point Surface Mount

Specifications

Dimensions	(H x W x D)
Surface Mount	88mm x 88mm x 54mm
Flush Mount	88mm x 88mm x 34mm
Operating Voltage	27 V AC
Switch Type	Single Pole Double Throw
Material	High Impact ABS
Operating Temp.	-20°C to +60°C
Humidity	0 – 95% non-condensing
IP Rating	Indoor Use Only
Weight	180g
Approvals	NZS4512:2003

Item Numbers

4255-0100	Conventional Red Surface Mount
4255-0150	Conventional Red Flush Mount
4255-0200	Addressable Red Surface Mount
4255-0250	Addressable Red Flush Mount